Square D (Schneider Electric) Homeline HOM48L125GRB, 125 A main-lug, 4 spaces/8 circuits, NEMA 3R, ground bar included



Dimensions	8.9″ W × 14.8″ H × 4.3″ D
Material	Welded galvannealed steel enclosure; tin-plated aluminum bus
Finish / colors	Baked enamel, gray
Electrical	volts: 120/240 V AC 1-ph 3-wire · amps: 125 · plug: Main lugs, 14 AWG to 2/0 AWG copper · breaker: Feeder breaker at the house panel (for example 60 A 2-pole) protects it; panel short-circuit rating 10 kA
Where it goes in UNIT5.xyz	Surface mount on a side wall stud bay (8.9 in wide), with the bottom at least 12 in above the slab; keep the NEC 110.26 working space clear (30 in wide x 36 in deep in front). Keep it off the front wall because of the door coil.
Warranty	18 months (Schneider datasheet)
Made in	Mexico

The manufacturer's spec sheet follows on the next page.

Product data sheet

Specifications



Load center, Homeline, 1 phase, 4 spaces, 8 circuits, 125A fixed main lugs, NEMA3R, gnd bar

HOM48L125GRB

Product availability: Stock - Normally stocked in distribution facility

Main

Product Type	Load Center
Marketing Trade Name	Homeline
Load Center Type	Fixed Mains (lugs)
Rated Current	125 A
Number of Spaces	4
Maximum Number of Single Pole Circuits	8
Enclosure Rating	NEMA 3R weatherproof enclosure
Cover Type	Surface cover
Electrical Connection	Lugs
Provided Equipment	Grounding bar 1)

Complementary

Max Short Circuit Current Rating	10 kA
Maximum Number of Tandem Breakers	4
Number of Phases	1 phase 3 wires
Voltage Rating	120/240 V AC
Wire Size	14 AWG...2/0 AWG copper 12 AWG...2/0 AWG aluminium
Ground Bar	Grounding bar included (not installed)
Busbar Material	Tin plated aluminium: busbar
Enclosure Material	Welded galvannealed steel
Surface Finish	Baked enamel Gray
Box Number	15R
Bus Rated Current	125.0 A
Height	14.8 in (376 mm)
Width	8.9 in (226 mm)
Depth	4.3 in (108 mm)

Environment

Ambient Air Temperature for Operation	23 °F (-5 °C) 104 °F (40 °C)
Product Certifications	UL listed file E-6294

Price is “List Price” and may be subject to a trade discount – check with your local distributor or retailer for actual price.

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

Category	US1DE3C00149
Discount Schedule	DE3C
GTIN	785901484370
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Nbr. of units in pkg.	1
Package 1 Height	5.100 in (12.954 cm)
Package 1 Width	10.300 in (26.162 cm)
Package 1 Length	16.300 in (41.402 cm)
Package weight(Lbs)	11.171 lb(US) (5.067 kg)
Unit Type of Package 2	PAL
Number of Units in Package 2	72
Package 2 Height	38.000 in (96.520 cm)
Package 2 Width	40.000 in (101.600 cm)
Package 2 Length	48.000 in (121.920 cm)
Package 2 Weight	846.0004 lb(US) (383.739 kg)

Contractual warranty

Warranty (in months)	18

Environmental Data

Schneider Electric aims to achieve Net Zero status by 2050 through supply chain partnerships, lower impact materials, and circularity via our ongoing “Use Better, Use Longer, Use Again” campaign to extend product lifetimes and recyclability.

Environmental Data explained >

How we assess product sustainability >

Environmental footprint

Total lifecycle Carbon footprint	**24 kg CO2 eq.**
Carbon footprint of the manufacturing phase [A1 to A3]	**22 kg CO2 eq.**
Carbon footprint of the distribution phase [A4]	**2 kg CO2 eq.**
Carbon footprint of the installation phase [A5]	**0.1 kg CO2 eq.**
Carbon footprint of the use phase [B2, B3, B4, B6]	**0.1 kg CO2 eq.**
Carbon footprint of the end-of-life phase [C1 to C4]	**0.3 kg CO2 eq.**
Environmental Disclosure	**Product Environmental Profile**

Use Better

Materials and Substances

Packaging made with recycled cardboard	**Yes**
Packaging without single use plastic	**No**
EU RoHS Directive	**Compliant**
REACh Regulation	**Free of Substances of Very High Concern above the threshold**
California proposition 65	**WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov**

Use Again

Repack and remanufacture

Recyclability potential, in %	**90**
Circularity Profile	**No need of specific recycling operations**
Take-back	**No**

Image of product / Alternate images

Alternative

